

Declaration of Performance
CE DOP 10/105393/10



The undersigned, representing the following:

Company placing on the market:
NSG Group European Technical Centre Hall Lane Lathom Nr Ormskirk Lancashire L40 5UF

Manufacturing Plant:
Pilkington Deutschland AG, Gelsenkirchen, Germany (Addresses of other sites kept on record)

Herewith declare that the following product:
Pilkington **Pyrodur®** Plus 30-104, 7 mm

is in conformity with the provisions of the following EU Regulation when installed in accordance with the installation instructions contained in the product documentation:
Regulation (EU) No 305/2011 Construction Products Regulation.

The following product standard referenced below has been applied:
EN 14449: Glass in building - Laminated glass and laminated safety glass - Evaluation of conformity/Product standard EN 1279-5: Glass in building – Insulating glass units - Part 5: Evaluation of conformity/Product standard

Declared Performance

Essential Characteristics	AVCP Systems	Vlastnosti
Odolnost proti požáru	1	EI15/EW30
Reakce vůči požáru	3,4	B-s1, d0
Požární vlastnosti	3,4	NPD
Odolnost proti průstřelu	1	NPD
Odolnost proti explozi	1	NPD
Odolnost proti ručně vedenému útoku	3	NPD
Odolnost proti nárazu - kyvadlová zkouška	3	2(B)2
Odolnost proti náhlým změnám teplot a teplotním rozdílům	4	40 K
Odolnost proti zátěži - vítr, sníh - trvalému a užitnému zatížení	4	NPD
Izolace proti přímému hluku z letecké dopravy	3	35 (-1; -3) dB
Termické vlastnosti	3	5.5 W/m ² K
Vlastnosti záření		
Prostup světla a světelná reflexe	3	0.89/0.08/0.08
Prostupnost a reflexe slunečního záření	3	0.75/0.07/0.07
g Value	3	0.8
Durability	3,4	Pass

Notified production control certification body number
1121, 0432, 0757, 1750, 1234, 1004, 1680, 2509, 1314, 1488, 1812, 0833



Martin Neifer
Operations Director Fire Protection Glass
01/07/2013



Nils Brinkmann
Commercial Director Fire Protection Glass
01/07/2013